

Anzac

2330/2331 *Dot Matrix printer*

The Anzac 2330/2331 printers offer fast, quiet desktop performance to users of IBM's Systems 3X and AS/400 computers. Three paper paths; automatic forms loading; automatic forms ejection (document on demand) for both continuous and cut sheet stationery; automatic paper thickness detection and printhead adjustment. Featuring direct twinaxial attachment via a smart "T" connector, the Anzac 2330/2331 printers are out of the box and running within five minutes.

Winning features in more detail:

Three paper paths.

Two continuous paper paths, both with automatic loading and parking. A manual cut sheet paper path for either single or multipart individual forms.

Perfect Paper Management.

No more manual loading and unloading forms. Paper changes are as simple as moving a lever. Leave forms parked in both continuous paper paths while you use the manual cut sheet paper path. Then simply move a lever to select either of the parked continuous paper paths for instant forms reloading and printing. Or park the current continuous form, and load the alternative continuous form from its parked position in the second continuous paper path for immediate printing.

Automatic paper thickness

adjustment. When loading a new form, the Anzac 2330/2331 automatically senses the form's thickness, and adjusts the printhead to the correct position for perfect print quality every time. No more manual adjustments.

Zero-to-any tear (document on demand) on any paper path.

Print on the very first line from any paper path, or set each paper path with its own automatic load position. For example, the single sheet forms can be set to load one inch beyond the top of form, one continuous paper path could be set for half inch, and the other continuous path set to print at line one. The Anzac 2330/2331 remembers each individual loading position, and will always load to the same position.

Speed.

Printing 427 characters per second, the Anzac 2330/2331 speeds quietly through reports on single sheet paper or invoices on 5 part stationery.

Clip-in ribbons.

For clean-hand ribbon changes in seconds, the Anzac 2330/2331 printers have the cleanest ribbon change of any printer ever built. The ribbon cartridge is an automatic re-inking ribbon, with a four million character life.

Bar codes.

The Anzac 2330/2331 prints sixteen different bar codes, including POSTNET. These are printed using AAPF, Anzac's high level plain text language, which is compatible across Anzac's dot matrix and laser printers. Same command, same result.

Noise level.

At 53dB(A), the Anzac 2330/2331 printers are among the quietest in the business. Create a pleasant work environment for all the staff with whisper-quiet printing.

Anzac support and maintenance.

Long known for its outstanding maintenance and support operation, Anzac staff are no further than an 800 call away from solving your problems. Ask around, and don't be surprised at the good things you hear. Anzac is the printer supplier of choice for many of the world's largest companies because of the excellent long term support Anzac provides.



www.anzacom.com

2330/2331 *Dot Matrix printer*

SPECIFICATIONS

2330

2331

TYPE

9 Pin Dot Matrix

9 Pin Dot Matrix

PRINT SPEED

High Speed Draft

427 CPS

427 CPS

Utility

320 CPS

320 CPS

Near Letter Quality

80 CPS

80 CPS

16 BARCODES

UPCA, UPCE, EAN/JAN 13, EAN/JAN8, Code 3 of 9, Extended Code 3 of 9, Code A Bar, EPC E 6, Code 93, Extended Code 93, Code 2 of 5, Code 128, MSI, UCC 128, ZIP/POST NET, BANKNET.

PAPER HANDLING

Number of sheets

5

5

Maximum Thickness

Rear Feed .014" (0.36 mm)

.014" (0.36 mm)

Bottom Feed .017" (0.44 mm)

.017" (0.44 mm)

Slew Rate 5.0 ips

5.0 ips

Push tractor & paper parking YES

YES

PAPER PATH

Rear (push tractor)

YES

YES

Bottom (push tractor)

YES

YES

Top (cut sheet)

YES (manual)

YES (manual)

SIZE

Width

17.0"

23.0"

Depth

15.0"

15.0"

Height

6.5"

6.5"

Weight

17lb. 10oz.

23lb. 2oz.

DUTY CYCLE

20,000 Pages per month

20,000 Pages per month

INTERFACE

Twinax

Internal, with LED and software diagnostics

Emulation

5225-1 (Standard)

5225-1 (Standard)

4214-2 (Optional)

4214-2 (Optional)

NOISE LEVEL

Normal

53 dB(A)

53 dB(A)

Quiet

50 dB(A)

50 dB(A)

RIBBON LIFE

On average, 10 cpi utility 4 Million characters

4 Million characters



510.670.0734 Direct.

510.670.1442 Fax

www.anzacom.com